

/ grand majestic.

BERRY  ALLOC

**For those
'think big'
moments.**



_____ high pressure floors.

Celebrate the majesty of nature with our extra-long and super-wide planks.

Grand Majestic welcomes the majesty of unique super-wide and extra-long planks for a strong and beautiful floor. With its 2,4 m long and 30 cm wide planks, this brand new collection creates a wonderful feeling of open space.

Through timeless and elegant wood decors, Grand Majestic captures the calming and soothing force of nature in a floor that can handle everything life throws at it.



Natural & elegant.





high pressure
extremely
durable



AluLoc



extra
long



extra
wide



water
resistant



lifetime
warranty
residential



SilentSystem



katla natural honey

Made to last, made for life.

Durable and water resistant, this irresistible premium quality floor is ideal for busy spaces.

Collection guide.

Pick your colour



etna light brown
62001986



etna brown
62001987



etna dark brown
62001988



katla natural
62001990



katla nordic
62002107



katla natural honey
62001991

Pick your **accessories**



60 mm matching skirting

Modern skirting to create a perfectly matched wall finish.

Installation: glue or clips

Skirtings: 2400 x 14 x 60 mm
(L x W x H)



T-profile matching

Matching transition profile between 2 floors of the same height.

T-profiles: 2400 x 44 mm (L x W)

Adjustable to laminate height
of 9 – 13 mm



How to install?

The floor must be able to move in all directions after installation. Therefore, certain guidelines must be followed:

- Do not screw, glue or wedge the floor so it can't move: free flow is important. FillerTwine (resilient poly foam) is used in gaps to keep the floor mobile.
- Distance to wall and fixed constructions is 4 mm, regardless of the area.
- Use skirting with a minimum width of 14 mm. T-profiles must be used when transitioning to a new room.

Kitchen cabinets, islands and other fixtures should not be installed on top of the floor. The end joints must be staggered by at least 1/3rd of a floorboard.

When determining the direction of your floor prior to installation, consider the following:

- The longitudinal direction of the room.
- Light input from windows.
- Longitudinal direction of the roof panel

Technical guide

grand majestic



Dimensions	EN 13329	2410 x 303 mm
Total thickness (incl. underlay)	EN 13329	12,3 mm
Thickness of the wear layer	EN 24340	0,6 mm
Click system		AluLoc
Total weight		22,3 kg
Usage classification	EN 13329	23/34
Integrated underlay		SilentSystem
Underfloor heating		suitable max. 27°C (80°F), electrical heating systems max. 60 W/m ²
Thermal resistance	DIN 52612-3	0,13 m ² K/W
Static electrical propensity	EN 1815	< 2,0 kV (antistatic)
Abrasion resistance	EN 13329	AC 6 (IP > 8500)
Impact resistance	EN 13329	> 2000 mm, > 25 N
Thickness swelling	EN 13329	< 7%
Resistance to staining	EN 438.2.26	5
Formaldehyde	EN 717-1	< 0,03 mg/ m ³ (M1)
Fire resistance	EN 13501-1	Bfl-s1
Castor chair	EN 425	No visible damage
Furniture leg	EN 424	No visible damage
Slip resistance	EN 13893	Class DS
Sound reduction: impact sound	EN 717-2	19 dB
Residential warranty		Lifetime
Commercial warranty		10 year
1 box		3 planks – 2,1907 m ²
1 pallet		42 boxes – 92,01 m ²

**Inspiration, tutorials, installation instructions
and much more available here:**





FILTER COFFEE	2.5
ESPRESSO	2.5
SINGLE ORIGIN COFFEE	A.Q.
MACCHIATO	3
ONE AND ONE	3.5
CAPPUCCINO	3.5
LATTE	4
MOCHA	5
CHAI	4
TEA	A.Q.

katla nordic

Strength & size.

Designed and made in Norway, Grand Majestic represents the latest evolution of progressive technology for BerryAlloc's High Pressure Floors range. By merging trendsetting aesthetics with high quality, Grand Majestic is the pinnacle of our HPF innovation: the world's strongest floor with extraordinary plank dimensions – and yet still easy and simple to care for.



etna light brown

BERRY  **ALLOC**

Alloc AS

Fiboveien 26
4580 Lyngdal - Norway
T +47 38 34 22 00
info@berryalloc.com

www.berryalloc.com