

Installation Rocko Flooring with PerfectPad®

1 Humidity 40 - 60 %
15-30°C / 59-86°F
48h
≤ 200 mm/8"

2 ≥ 0,2 mm PE

3 1m / 40"
max. 2 mm / 1 m
max. 0,08" / 40"

4 !

5 !

6

7 CONCRETE MAX 2,0 CM %
ANHYDRITE MAX 0,5 CM %
HEATING:
CONCRETE MAX 1,5 CM %
ANHYDRITE MAX 0,3 CM %

8 !
max. 27°C / max. 81°F

9 !

10 PE FOIL
min. 0,2 mm PE

11 ca. 2 cm / 4/5 inch
ca. 20 cm / 8 inch

12 min. 0,2 mm PE

13 !

14

15 10mm/0,4"

16

17

18 10mm / 0,4"
180°
or

19 10mm / 0,4"
180°

20 2 ≥ 400 mm/16"
180°

21a 10mm/0,4"
10mm/0,4"

21b 10mm/0,4"
10mm/0,4"

22

23 !
10mm / 0,4"
180°

24 Ø X
Ø X+20mm/0,8"

25

26 PVC adhesive

27 180°

28 10 mm/0,4"
180°

29 180°

30 180°

31a !
400 - 500 mm/16 - 20"

31b !
PVC

32 Silicone
wet rooms / piscinas húmedas

33

34 OIL WAX POLISH

35

More information:



www.rocko-vinyl.com