





Altro Marine™ 20 / T20


Like Altro Marine?
Love Altro's shoe
and barefoot ranges



Steam | IPT20807
WR85 / A1M85 / LRV 37



Rainfall | IPT20810
WR135 / A1M135 / LRV 38



Cascade | IPT20809
WR105 / A1M01 / LRV 71




Gull | T20813
WR79 / A1M191 / LRV 46




Marlin | T20811
WR203 / A1M203 / LRV 34




Reef | T20801
WR20 / A1M20 / LRV 41



Shark | IPT20812
WR201 / A1M84 / LRV 24



Tide | IPT20808
WR71 / A1M71 / LRV 21



Seagrass | IPT20814
WR137 / A1M137 / LRV 37

Love Altro's shoe and barefoot ranges


Altro Aquarius

Altro Pisces



Request your Altro Aquarius™ or Altro Pisces™ sample card now

+44 (0) 1462 707 700 samples@altro.com






















Fen | IPT20815
WR242 / A1M242 / LRV 19



Typical applications

Shower cubicles. Swimming pool foot bath. Swimming pool surrounds.

Technical information

	Fire behaviour tested in acc. with	EN ISO 9239-1 EN ISO 11925-2 EN 13501-1	≥ 8 kW/m ² Pass B _f -s1
	Slip resistance	EN 13893 EN 13845 Annex C EN 16165 Annex B / ASR A1.5 EN 16165 Annex A	≥ 0.30 / DS ESb R10 C
	Sound insulation	EN ISO 140-8	ca. 13 dB
	Flooring type	EN 13845	Safety flooring
	Thickness	EN ISO 24346	2 mm
	Wear layer thickness	EN ISO 24340	2 mm
	Roll dimensions	EN ISO 24341	2 m x 20 m = 40 m ²
	Weight	EN ISO 23997	2.8 kg/m ²
	Residual indentation	EN ISO 24343-1	≤ 0.10 mm
	Classification for use	EN ISO 10874	34, 43
	Flexibility	EN ISO 24344	Pass
	Dimensional stability	EN ISO 23999	≤ 0.4 %
	Light fastness	EN ISO 105-B02	≥ 6
	Castor chair abrasion	ISO 4918	Yes, type W
	Wear resistance	EN 13845 Annex D	≤ 10% / 50000 cycles
	Chemical resistance	EN ISO 26987	Good
	Underfloor heating	EN 12524	Suitable
	Electrical behaviours	EN 1815	≤ 2 kV, antistatic
	VOC emissions	CDPH 1350 / Floorscore	Approved



Altro Limited a company certified by SGS to ISO 9001 and ISO 14001.



1029
EN 14041



0120
EN 14041



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).



Sustainability



1A+ BRE generic green guide rating for resilient flooring, full details available at www.thegreenguide.org.uk



EN 15804 SD207
EPD No.: 000255



Installation and maintenance

Please refer to Altro installation and maintenance instructions. Failure to follow these instructions can affect product performance and may affect or invalidate Altro's product guarantee. Technical information on installation and maintenance (including cleaning and staining) can be found at www.altro.com

Light Reflectance Values measured in accordance with BS 8493:2008. Exact material match with samples cannot be guaranteed.

Codes: WR = weld rod, A1M = mastic, LRV = light reflectance value

Request your Altro Aquarius or Altro Pisces sample card now – ☎ 01462 707 700 ✉ samples@altro.com

 Altro, Altro Marine, Altro Aquarius, Altro Pisces and Altro Easyclean Technology are trademarks of Altro Limited.

United Kingdom

☎ +44 (0) 1462 707 700

✉ enquiries@altro.com

Australia

☎ +61 3 9764 5666

✉ info@asf.com.au

Subject to alteration.